

Response
10/034,959
Page 2 of 11

Pending Claims

1. (Original) A method of treating a female patient for urinary stress incontinence, comprising:
per vaginally inserting a bone anchor to enter the posterior wall of the pubic bone, said bone anchor comprising suture thread secured thereto; and, using said suture thread and a sling to treat the incontinence.
2. (Original) A method as claimed in claim 1, wherein said suture thread and said sling are used to position the bladder neck of the patient.
3. (Original) A method as claimed in claim 1, wherein said suture thread and said sling are used to position the urethra of the patient.
4. (Original) A method as claimed in claim 1, wherein said suture thread and said sling are used to position the bladder neck and the urethra of the patient.
5. (Previously presented) A device for securing a suture to a suture attachment site in a patient comprising:
a body having a suture entrance and a suture exit;
a motive suture delivery mechanism disposed within said body; and,
said motive suture delivery mechanism including a sensory feedback element indicative of delivery of said suture to said suture attachment site.
6. (Previously presented) A device according to claim 5, wherein said sensory feedback element is an audible tone.
7. (Previously presented) A device according to claim 6, wherein said audible tone is a changing audible tone.

BEST AVAILABLE COPY

AMS - 036
Our File: 58286-306513

Response
10/034,959
Page 3 of 11

8. (Previously presented) A device according to claim 7, wherein said changing audible tone is generated by said motive suture delivery mechanism.
9. (Previously presented) A device according to claim 8 wherein said motive suture delivery mechanism includes a battery powered motor.
10. (Previously presented) A device according to claim 5 wherein the body is sized and shaped to anchor the suture on a posterior portion of a patient's pubic bone.
11. (Previously presented) A device according to claim 5, wherein said sensory feedback element is a visual indicator.
12. (Previously presented) A device for securing a suture to a suture attachment site in a patient comprising:
 - a body having a suture entrance and a suture exit;
 - a motive suture delivery mechanism disposed within said body;
 - said motive suture delivery mechanism including a sensory feedback element indicative of delivery of said suture to said suture attachment site;
 - wherein said sensory feedback element is a visual indicator, and
 - wherein said visual indicator includes cessation of twisting of said suture.
13. (Previously presented) A method of securing a suture to a suture attachment site in a patient comprising:
 - identifying a suture attachment site in said patient;
 - directing said suture proximate to said site;
 - initiating delivery of said suture to said site;
 - awaiting sensory indication of delivery of said suture to said suture attachment site;
 - discontinuing said delivery of said suture upon receiving said sensory indication.

AMS - 036
Our File: 58286-306513

Response
10/034,959
Page 4 of 11

14. (Previously presented) A method as set forth in claim 13, wherein said receiving of said sensory indication includes receiving an audible tone.
15. (Previously presented) A method as set forth in claim 13, wherein said receiving of said sensory indication includes receiving a change in said audible tone.
16. (Previously presented) A method as set forth in claim 13, wherein said receiving of said sensory indication includes observing a visual indicator.
17. (Previously presented) A method of securing a suture to a suture attachment site in a patient comprising:
- identifying a suture attachment site in said patient;
 - directing said suture proximate to said site;
 - initiating delivery of said suture to said site;
 - awaiting sensory indication of delivery of said suture to said suture attachment site;
 - discontinuing said delivery of said suture upon receiving said sensory indication;
 - wherein said receiving of said sensory indication includes observing a visual indicator, and
 - wherein said receiving of said sensory indication includes observing a substantial cessation of suture twisting.
18. (Previously presented) A device for delivering a bone anchor with an associated suture to a patient, the device comprising:
- a body that is sized and shaped to deliver the anchor and associated suture to a posterior portion of a patient's pubic bone through vaginal incision,
 - the device having a suture entrance and a suture exit;
 - a bone anchor delivery mechanism associated with said body; and,

AMS - 036
Our File: 58286-306513

Response
10/034,959
Page 5 of 11

the device including a sensory feedback element indicative of delivery of said bone anchor with associated suture to the posterior portion of the patient's pubic bone.

19. (Previously presented) A device according to claim 18, wherein the bone anchor includes a bone screw.
20. (Previously presented) A device according to claim 18, wherein said sensory feedback element is an audible tone.
21. (Previously presented) A device according to claim 20, wherein said audible tone is a changing audible tone.
22. (Previously presented) A device according to claim 21, wherein said changing audible tone is generated by said bone anchor delivery mechanism.
23. (Previously presented) A device according to claim 18, wherein said sensory feedback element is a visual indicator.
24. (Previously presented) A device for delivering a bone anchor with an associated suture to a patient, the device comprising:
 - a body that is sized and shaped to deliver the anchor and associated suture to a posterior portion of a patient's pubic bone through a vaginal incision,
 - the device having a suture entrance and a suture exit;
 - a bone anchor delivery mechanism associated with said body;
 - the device including a sensory feedback element indicative of delivery of said bone anchor with associated suture to the posterior portion of the patient's pubic bone;
 - wherein said sensory feedback element is a visual indicator, and
 - wherein said visual indicator includes cessation of twisting of said suture.

AMS - 036
Our File: 58286-306513

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.